


On when it
matters most.

Rail Operations



Dialight



Vigilant 26K Floodlight

Vigilant 26K Highbay



Vigilant 26K Floodlight

Vigilant 26K Highbay

CAUTION
WATCH FOR WORK
VEHICLES

WARNING
BELL MUST BE SOUNDED
AT LEAST 15 SECONDS
BEFORE MOVING

SPEED
LIMIT **6**

LIMITED
CLEARANCE

If you do not work within RSM
please contact your escort or RSM supervisor

Escort	Vehicle ID	Destination	Time

KEEP OUT
AUTHORIZED
ENTRY ONLY

Vigilant 60K Highbay

Vigilant 26K Floodlight



Vigilant 60K Highbay

Vigilant 26K Floodlight





MAINTENANCE LUBRICATION BAY

- 1. Check the oil level in the reservoir tank to top it up.
- 2. The oil level should be at a certain level.
- 3. Do not overfill with oil as it will cause the pump to fail.
- 4. Do not use oil of a different grade.
- 5. Do not use oil of a different brand.
- 6. Do not use oil of a different color.
- 7. Do not use oil of a different viscosity.
- 8. Do not use oil of a different type.
- 9. Do not use oil of a different weight.
- 10. Do not use oil of a different brand.
- 11. Do not use oil of a different color.
- 12. Do not use oil of a different viscosity.
- 13. Do not use oil of a different type.
- 14. Do not use oil of a different weight.
- 15. Do not use oil of a different brand.
- 16. Do not use oil of a different color.
- 17. Do not use oil of a different viscosity.
- 18. Do not use oil of a different type.
- 19. Do not use oil of a different weight.
- 20. Do not use oil of a different brand.

MAINTENANCE TO COMPLY WITH THESE INSTRUCTIONS WE MUST USE A QUALITY OIL.

HEARING PROTECTION MUST BE WORN IN THIS AREA

Vigilant 26K Floodlight



-SAFE ZONE-

1/2 4
B27
405TT292

Vigilant 18K Floodlight



CAUTION
WATCH FOR WORK
VEHICLES

WARNING
BELL MUST BE SOUNDED
AT LEAST 15 SECONDS
BEFORE MOVING

SPEED
LIMIT **6**
MPH

LIMITED
CLEARANCE

BEWARE
LOCOS

BEWARE
LOCOS



Vigilant 26K Floodlight

66w LED Linear

Albeck

Pilbara Iron
A member of the BHP Group

M.R.C. Max
Main
Aux



Onsite
Steel Services

STEEL

